



RIDE WITHOUT TENSION

GMAX 4T

SAE 20W50

A premium grade motorcycle oil developed for the lubrication of all four-stroke engines. Formulated from high viscosity mineral oils blended with additives to provide quality performance in four-stroke motorcycle engines.

APPLICATIONS:

It is highly recommended for standard four-stroke motorcycle engines requiring API SL JASO MA and lower classifications.

PERFORMANCE FEATURES:

- Enhanced engine protection
- Controls engine wear.
- Effective protection from rust and corrosion
- Excellent detergent / dispersant capability

TYPICAL PHYSICAL AND CHEMICAL CHARACTERISTICS

SAE Viscosity Grade	20W50
Viscosity @ 40°C cSt	165
Viscosity @ 100°C cSt	17.9
Viscosity index	120
Density, kg./li	0.880
Flash Point, °C	250
Water Solubility	Insoluble
Physical State	liquid
Appearance	Clear
Color	Amber
Odor	Mild

HEALTH & SAFETY

This product will not pose a safety health hazard if used properly and industrial safety practices are observed. As with all industrial lubricants, avoid prolonged contact with skin, especially with used oils. Wash hands with soap and water after contact. Take used oil to a recycler. Do not discharge in the environment.

PACKAGING:

18 liter pail and 200 liter drum.