



RIDE WITHOUT TENSION

GMAX ATF 3

AUTOMATIC TRANSMISSION FLUID GM DEXTRON III

A premium-quality transmission fluid specially formulated for automatic and power shift transmission and some power steering application where a GM Dexron III specifications are recommended.

APPLICATIONS:

- Automatic transmission and hydraulic systems where a fluid type of Dexron III is required/specified
- Automatic and power-shift transmission and torque converters of passenger cars, light commercial vehicles and some heavy equipment.

PERFORMANCE STANDARDS

Meets all Ford and General Motors Automatic Transmission requirement except Dexron VI, Ford Mercon V, and Type F Fluid.

TYPICAL PHYSICAL AND CHEMICAL CHARACTERISTICS

Density, kg./li	0.860
Viscosity @ 40°C cSt	34
Viscosity @ 100°C cSt	7.5
Viscosity index	200
Flash Point, °C	170
Appearance	Clear
Color	Red
Odor	Mild

HEALTH & SAFETY

This product will not pose a safety health hazard if used properly and industrial safety practices are observed. As with all industrial lubricants, avoid prolonged contact with skin, especially with used oils. Wash hands with soap and water after contact. Take used oil to a recycler. Do not discharge in the environment.

PACKAGING:

18 liter pail and 200 liter drum.