



RIDE WITHOUT TENSION

## GMAX POWER HD

**SAE 40API CF/SF**

A high-performance, heavy-duty monograde engine oil designed to provide premium quality service in both turbocharged and naturally aspirated diesel and petrol engines. It is formulated with advanced additive technology to resist oil thickening by minimizing sludge formation and effectively keeps particles in suspension to extend filter life.

### APPLICATIONS:

- Suited for all turbocharged and naturally aspirated diesel engines of trucks, heavy equipment machineries. and locomotives
- Also suitable for stationary diesel engines
- In some applications, also suited for gearboxes, torque converters, and hydraulic systems that require the properties of an engine oil

### PERFORMANCE STANDARDS:

API CF/CD/CC/SF

### TYPICAL PHYSICAL AND CHEMICAL CHARACTERISTICS

<b>SAE Viscosity</b>	<b>40</b>
Density, kg./li	0.875
Viscosity @ 40°C cSt	160
Viscosity @ 100°C cSt	15.3
Viscosity index	107
Flash Point, °C	255
Water Solubility	Insoluble
Physical State	Liquid
Appearance	Clear
Color	Amber
Odor	Mild

### HEALTH & SAFETY:

This product will not pose a safety health hazard if used properly and industrial safety practices are observed. As with all industrial lubricants, avoid prolonged contact with skin, especially with used oils. Wash hands with soap and water after contact. Take used oil to a recycler. Do not discharge in the environment.

### PACKAGING:

18 liter pail and 200 liter drum.