

GMAX POWER HDX

SAE 15W-40API CF-4/SG

A high-performance, premium-quality multigrade engine oil specially developed to meet and exceed required quality service in both turbocharged and naturally aspirated diesel and petrol engines. It is formulated with an excellent viscosity index property that makes it suitable for longer oil drain intervals.

APPLICATIONS:

- Suited for all turbocharged and naturally aspirated diesel engines of trucks, heavy equipment machineries.
 - Automotive diesel engines using fuels with considerable sulfur content.

PERFORMANCE STANDARDS:

- API CF-4/SG

PHYSICAL AND CHEMICAL CHARACTERISTICS

SAE Viscosity	15W40
Viscosity @ 40°C cSt	110
Viscosity @ 100°C cSt	15.6
Viscosity index	151
Density, kg./li	0.885
Flash Point, °C	228
Water Solubility	Insoluble
Physical State	Liquid
Appearance	Clear
Color	Amber
Odor	Mild

HEALTH & SAFETY:

This product will not pose a safety health hazard if used properly and industrial safety practices are observed. As with all industrial lubricants, avoid prolonged contact with skin, especially with used oils. Wash hands with soap and water after contact. Take used oil to a recycler. Do not discharge in the environment.

PACKAGING:

18 liter pail and 200 liter drum.