

GMAX POWER ULTRA

SAE 15W-40API CI-4/SL

Super premium-quality, high-performance multi grade engine oil specially formulated for the demanding requirements of most on-and-off-road engine application. It is also ideal for use on turbocharged and supercharged diesel engines.

APPLICATIONS:

- Suited for all turbocharged and supercharged diesel engines operating at lower-speed

high-load engines

- Also suited for petrol, CNG, LPG-operated engines that require its usage properties

PERFORMANCE STANDARDS:

- API CI-4/CH-4/CG-4/CF-4/CF/SL
- ACEA E5/B3
- MAN M3275
- MB 228.3
- MACK EO-M+
- Volvo VDS-3

PHYSICAL AND CHEMICAL CHARACTERISTICS

SAE Viscosity	15W40
Viscosity @ 40°C cSt	112
Viscosity @ 100°C cSt	16.0
Viscosity index	153
Density, kg./li	0.885
Flash Point, °C	229
Water Solubility	Insoluble
Physical State	Liquid
Appearance	Clear
Color	Amber
Odor	Mild

HEALTH & SAFETY:

This product will not pose a safety health hazard if used properly and industrial safety practices are observed. As with all industrial lubricants, avoid prolonged contact with skin, especially with used oils. Wash hands with soap and water after contact. Take used oil to a recycler. Do not discharge in the environment.

PACKAGING:

18 liter pail and 200 liter drum.