

## SUPER GMAX

### API SL/CF GASOLINE ENGINE OIL SAE 20W50

Multi-grade motor oil formulated from high viscosity index base oil and high-performance additives designed to meet the implemented exhaust emission standards to sustain engine durability.

#### APPLICATIONS:

- Fully formulated gas engine oil for gasoline and CNG/LPG fueled spark ignition engines where conventional API SL passenger car motor oils are recommended.
- For naturally aspirated and turbocharged petrol engines in passenger cars.
- Can be used for passenger car and light commercials diesel engines requiring **API CF** classification.

#### PERFORMANCE FEATURES:

- Dependable wear protection helps extend engine life.
- Excellent engine cleanliness, higher detergency.
- Reduces oil consumption.
- High oxidation resistance, longer oil life and greater resistance to oxidative thickening.
- Superior viscosity retention High 'VI' (Viscosity Index) ensures adequate viscosity at all operating temperatures

#### PERFORMANCE STANDARDS : API SL/CF

#### TYPICAL PHYSICAL AND CHEMICAL CHARACTERISTICS

SAE Viscosity Grade	20W50
Density, kg./li	0.871
Viscosity @ 40°C cSt	160
Viscosity @ 100°C cSt	18.0
Viscosity index	125
Flash Point, °C	240
Water Solubility	Insoluble
Physical State	Liquid
Appearance	Clear
Color	Red
Odor	Mild

#### HEALTH & SAFETY:

This product will not pose a safety health hazard if used properly and industrial safety practices are observed. As with all industrial lubricants, avoid prolonged contact with skin, especially with used oils. Wash hands with soap and water after contact. Take used oil to a recycler. Do not discharge in the environment.

#### PACKAGING:

18 liter pail and 200 liter drum.